

## **GACO ROOFTAPE SELF ADHESIVE SEAM TAPE**

### **Description:**

Gaco RoofTape is made of lightly cross linked polymers of butyl and E.P.D.M. rubber coated on fleece backing. Gaco RoofTape maintains its elasticity and splice integrity when subjected to severe ultraviolet rays, thermal shock, ponding water, and extremely low temperatures.

### **Usage:**

Gaco RoofTape seam sealing tape is pressure sensitive and is intended for sealing seams, fasteners and penetrations before GacoRoof Silicone roof coating is applied.

### **Color:**

Fleece backing is white, Adhesive is light tan.

## **APPLIED PRODUCT DATA**

### **Tensile:**

ASTM D-412 @ 2"/min: 35 psi

### **Elongation:**

250%

### **Adhesion:**

180°Peel

- Galvanized: 21 pli
- Stainless Steel: 20 pli

## **PACKAGED PRODUCT DATA**

### **Packaging:**

2 inches wide, 50 feet per roll.

### **Thickness:**

30 Mils

### **Shelf Life:**

18 Months

## **APPLICATION**

### **Application:**

Surfaces must be clean and dry. Cut tape to desired length and peel off release liner. Centre tape over seam and firmly press into place, removing all buckles and bubbles. If applying over fasteners, press tape over all sides to conform tape to the shape of the fastener. If more than one piece of tape is going to be used, overlap any adjoining pieces of tape by a minimum of 1/2". To prevent dirt pick-up, Gaco seam sealing tape must not be left exposed. The tape should be coated with GacoRoof Silicone Coating as soon as it is applied.

Gaco Roof Tape is distributed in the UK & Ireland by Igoe International Ltd,  
UK, 93-99 Mabgate Business park, Leeds LS9 7DR. (0845) 555 88 01  
Ireland 135 Slaney Road, Dublin Industrial Estate, Glasnevin, Dublin 11, Ireland.  
Tel 00 353 1 830 22 50 Fax 00353 1 8300 770 Email: [info@igoe.ie](mailto:info@igoe.ie)